

JMY628C IC Card Reader

User's manual

(Revision 3.50)

Jinmuyu Electronics Co. LTD

2012/3/2





Contents

1	Product introduction	2
2	Characteristics	2
3	Physical parameter and pin outs	3
3.1	Photo.....	3
3.2	Dimension	4
3.3	Pin configurations and Pin outs	4
3.4	Model available	5
3.5	Model rule	5
3.5.1	Model format	5
3.5.2	Card operating type	5
3.5.3	Communication port.....	5



1 Product introduction

JMY628C is a RFID read/write module with UART, IIC or USB port. JMY628C has various functions and supports multi ISO/IEC standard of contactless cards. The RF protocol is complex, but the designer combined some frequent used command of RF card and then users could operate the cards with full function by sending simple command to the module.

The module and antenna is integrated. The impedance between RF circuit and antenna was tuned by impedance analyzer, and then the module has excellent performance and stability.

2 Characteristics

- PCD model: NXP RC523
- Working frequency: 13.56MHz
- Supported standard: ISO14443A, ISO14443B, Mifare Classic
- Card supported: Mifare 1K/4K, FM11RF08, Ultra Light, DesFire, Mifare ProX, SR176, SRI512, SRI1K, SRI2K, SRI4K, SRIX4K, T=CL CPU cards(both ISO14443A & ISO14443B).
- Anti collision ability: Full function anti collision; be able to process multi-cards; be able to set operate single card only
- Auto detecting card: Supported, default OFF. The default state can be set.
- SAM baud rate: 9600bps/38400bps/19200bps(default)/115200bps/57600bps.
- EEPROM: 512 Bytes
- Power supply: DC 5V ($\pm 0.5V$)
- Interface: IIC/UART//USB HID (select when place order)
- Communication rate:
 - IIC: 400Kbps
 - UART: 19.2Kbps/115.2Kbps
 - USB: USB 1.1 HID class
- Max. command length: JCP04 254 Bytes; JCP05 510 Bytes.
- Interface level: UART/IIC: 3.3V (TTL level; 5V tolerance)
- Power consumption: 150mA
- Operating distance: 80mm (depending on card and antenna design)
- Dimension: 50mm*50mm*7.5mm
- Weight: About 20g
- ISP: Supported
- Operating temperature: -25 to +85 °C
- Storage temperature: -40 to +125 °C
- RoHS: Compliant




3 Physical parameter and pin outs

3.1 Photo





3.2 Dimension



3.3 Pin configurations and Pin outs

Pin number	Function	Type	Description
1	RXD/SCL	Input	UART RXD / IIC SCL
2	TXD/SDA	Input/output	UART TXD / IIC SDA
3	D+	Input/output	USB D+
4	D-	Input/output	USB D-
5	VCC	Power	VCC
6	GND	Power	GND



3.4 Model available

- JMY628CI IIC interface
- JMY628CT UART interface, TTL level

3.5 Model rule

3.5.1 Model format

1	2	3	4
JMY	628	X	X

1: company code; 2: product series code; 3: card operating type; 4: communication port type

3.5.2 Card operating type

A: PCD is RC522, support ISO14443A and Mifare Class

C: PCD is RC523, support ISO14443A, ISO14443B and Mifare Class

3.5.3 Communication port

I: IIC

T: UART

U: USB(USB 1.1 HID class)